

# Yealink Handset Range

A summary of the Yealink Handsets Supported by VanillaIP - for pricing please contact your channel manager.

## T19E2

- 132x64-pixel graphical LCD
- Two-port 10/1000 Ethernet switch
- PoE support
- Headset support
- 6 feature keys
- Dual 10/100 Ethernet Ports



## T21E2

- 132x64-pixel graphical LCD with backlight
- Two-port 10/100M Ethernet switch
- PoE support
- Headset support
- 2 line keys with LED
- HD Voice – Supports wideband codec: G.722
- 6 navigation keys
- Dual 10/100 Ethernet Ports



## T23G

- 3 line display
- Backlit display
- 4 Context Sensitive Softkey
- HD Voice Quality -Supports Codec G.722
- 2 programmable keys,
- 23 hard keys,
- 2 indication LEDs
- Dial by Name Directory – Our service required
- PoE support



## T27P

- 240-120 – pixel graphical LCD with backlight
- PoE support
- HD Voice – Supports codec: G722
- 8 line keys with LED
- 6 navigation keys



## T29G

- 480 x 272-pixel colour display with backlight
- PoE support
- HD voice – supports
- 10 line keys with LED
- 6 navigation keys
- 8 feature keys
- RJ9 headset port



## T40P

- 132 x 64 – pixel graphical LCD with backlight
- 10/100mb Ethernet
- HD Voice: HD Codec, HD Speaker, HD Handset
- 3 line keys with LED
- 5 feature keys
- 8 navigation keys



## T41P

- 192 X 64 Pixel graphical LCD display
- 3 line IP phone
- Yealink Optima HD voice
- PoE support
- 6 line keys
- 5 feature keys
- 2 context sensitive keys
- Dual Ethernet ports
- RJ-11 port



## T42G

- Dual-port Gigabit Ethernet (Router & Switch)
- Optima HD voice wideband technology (G.722)
- 6 multi-functional physical line keys
- Large 2.7" graphical LCD with backlight (192 x 64-pixels)
- Up to 3 SIP accounts
- Integrated IEEE 802.3af Power over Ethernet (PoE)
- Headset ready
- Hearing aid compatible (HAC)



## T46G

- Large 4.3" Colour Screen (480 x 272-pixel)
- Intelligent directory search
- Dual-port Gigabit Ethernet (Router & Switch)
- Up to 6 SIP accounts
- 10 multi-functional physical line keys
- Wideband HD voice using G.722 codec
- Built-in USB port supports Bluetooth headset
- Integrated Power over Ethernet (PoE) IEEE 802.3af
- Supports 6x EXP40 expansion module
- Hearing aid compatible (HAC)



## T48G

- Large touch screen display (800 x 480 Pixels)
- Up to 6 SIP accounts
- Dual Gigabit Ethernet ports
- 1000 entry local phone book
- HD Wideband audio technology
- RJ9 port for corded headsets
- Electronic Hook Switch (EHS) support
- USB Port - Supports Bluetooth dongle for wireless headsets
- 3-Way conference ability
- Support for up to 6x Yealink EXP40 expansion modules
- Hearing aid compatible
- Power received through PoE



## T49G

- 8inch Colour LCD Touch Screen
- 2 mega -pixel HD Camera with privacy shutter
- HD Voice and Audio
- Built-in Wi-Fi and Bluetooth
- 1 x USB Port
- 1 x RJ9 headset port



## W52P

- HD sound with Wideband technology
- Up to 4 simultaneous external calls
- 5 DECT cordless handsets
- 5 VoIP accounts
- Colour backlit display with intuitive user interface
- 10 hours talk time
- 100 hours' standby time
- Integrated PoE
- Desktop or wall mountable



## W52H

- Extra handset for the W52P
- 4 concurrent calls
- 10 hours talk time
- Charger included.

